

ICT 200 Series

The smart and versatile desktop device designed for efficiency

- Provide merchants with a compact payment device using minimum countertop space.
- Offer a unique payment experience from an ergonomic, intuitive device.
- Accept all electronic payment methods including EMV chip & PIN, magstripe and NFC/contactless.
- Enable brand promotion with a color display and customization capabilities.



security



smartcard



magstripe



contactless



color display



connectivity

The iCT 200 Series supports multiple payment methods using minimum counterspace.

Highest Security

The iCT 200 Series meets the highest security requirements and is PCI PTS 2.x and 3.x certified with SRED and Open protocol modules. The optional PIN privacy shield provides additional PIN entry confidentiality.

All Payment Options

Offering EMV chip & PIN, magstripe & NFC/contactless payment, the iCT 200 Series also enables new NFC couponing and wallet applications.

Designed for Merchants

Among the world's smallest and lightest devices, the iCT 200 Series is designed for easy handling and robust daily use. The backlit keypad and color LCD display make PIN entry and menu navigation easy and intuitive. Large keys, power buzzer and visual indicators speed transactions and reduce PIN entry errors.

All Connectivity & Communication

Equipped with an unparalleled array of communication technologies such as high speed modem, Ethernet, GPRS or 3G, the iCT 200 Series delivers anytime, anywhere connectivity.

Brand Promotion

Brand promotion is empowered by a crisp color graphic display, software customization and hardware personalization options (top casing, printer cover flap or lens).

Telium 2

Powered by the Ingenico Group, Telium 2 technology is the result of 30 years' experience in the payment industry. Secure, highly integrated and fast, Telium 2 is the world's best platform for secure payment services. With advanced functions, it can easily manage more than 2,000 graphical libraries and handle new business service apps. Telium 2 is the fully scalable, reliable operating system embedded into Ingenico Group's 20 million terminals deployed worldwide.



| iCT 200 Series | | iCT 220 | iCT 250 |
|--|---|--|---|
| Processor | ARM 9 & ARM 7 | ● | ● |
| Memory | 16 RAM /16 Flash 16 RAM /128 Flash 32 RAM /128 Flash µSD Card | ● Option Option Option | Option ● ● Option |
| SAM | | Up to 3 | Up to 3 |
| Card reader | Smart card Magstripe Contactless | 1 + 2nd optional ● Option | 1 + 2nd optional ● Option |
| Display | Size & Resolution Backlit | Black and white 2.7" graphic 128 x 64 pixels ● | TFT color 2.7" QVGA 320 x 240 pixels ● |
| Terminal connectivity | Dial-up modem Ethernet GRPS or 3G | ● Option Option | ● ● Option |
| Keypad | Backlit operational keys Navigation keys | 15 4 | 15 4 |
| Audio | Buzzer | ● | ● |
| Thermal printer | Speed in lines/second | 18 l/s | 18 l/s |
| Connections on terminal | RS232 USB host USB slave Power supply connector | 1 (+1 optional) 1 1 1 | 1 (+1 optional) 1 1 1 |
| Power supply | External power supply | 230V 50Hz | 230V 50Hz |
| Terminal size | L x W x H | 7.28" x 3.26" x 2.48" | 7.28" x 3.26" x 2.48" |
| Weight | Terminal without paper roll/cable | 11.46 oz | 11.46 oz |
| Privacy shield | | Option | Option |
| Customization | Lens marking Printer cover flap Top casing | Option Option Option | Option Option Option |
| Connections on Magic Box (optional) | Power supply connector RS232 Line in Ethernet | 1 1 (+1 optional) 1 1 | 1 1 (+1 optional) 1 1 |
| Environment | Operating temperature Storage temperature Relative humidity, non-condensing | 41°F to 113°F 4°F to 131°F 85% HR at +104°F | 41°F to 113°F 4°F to 131°F 85% HR at +104°F |
| Security | Online & offline | PCI PTS 2.x & 3.x | PCI PTS 2.x & 3.x |

CORP-BR-ICT 200 Series-Product-EN-SEPT2014. All rights reserved. This document is not binding and the specifications above can be modified without prior consent. ©2014



www.ingenico.us

