

Excella™ MDX**Specifications & Configurations****Standard Configurations***

| Interface | Power | P/N |
|------------------|--------------|------------|
| USB/Ethernet | 110V / 240V | 22360001 |

Specifications***General information**

| | |
|-------------------|------------------------------------------------------------------------|
| Interface | High Speed USB 2.0 |
| Color | Gray |
| Dimensions | Height: 6 in (153mm) Width: 3.9 in (100mm) Length: 8.1in (206mm) |
| Weight | 2.8lbs (1.3kg) Includes power adapter, USB cable |

Specifications

| | |
|-----------------------------|----------------------------------------------------------------|
| Reference Standards | ANSI X9.27 |
| Power Input | 12 VDC regulated, 1.5 Amps |
| Document Size | 4"x 9" maximum |
| Check Scanning | Dual-sided |
| Image Resolution | 200 dpi (scaling to 100 dpi); Black/white and grayscale images |
| Image Compression | CCITT G4 or JPEG |
| Check Feed | Single-feed input |
| MICR Fonts Supported | E13-B and CMC-s7 |

Environment

| | |
|--------------------|------------------------------------|
| Temperature | |
| Operating | 0 °C to 50 °C (32 °F to 122 °F) |
| Storage | -30 °C to 70 °C (-22 °F to 158 °F) |
| Humidity | |
| Operating | 10% to 90% non-condensing |
| Storage | Up to 100% non-condensing |
| Altitude | |
| Operating | 0 -10,000 ft (0 - 3,048m) |

Storage

0 - 50,000 ft (0 - 15240m)

