



Processor	<ul style="list-style-type: none"> ■ AMD Geode LX800 w/CS5536 Companion Chip <ul style="list-style-type: none"> ● 32-bit x86 processor
Operating System	<ul style="list-style-type: none"> ■ Microsoft Windows Embedded CE 6.0 ■ Microsoft WEPOS, XP Embedded Support <i>(Linux may also be supported)</i>
Solid State Flash Storage	<ul style="list-style-type: none"> ■ 256 MB uDOC – Standard for CE ■ 4 GB uDOC - Standard for WEPOS
Volatile Memory	<ul style="list-style-type: none"> ■ Up to 2GB DDR RAM <i>(Two DIMM Sockets)</i> 256 MB Standard
Removable Flash Memory	<ul style="list-style-type: none"> ■ Standard 50 Pin Type 1 Compact Flash <i>(Expandable to 8 GB)</i>
Networking	<ul style="list-style-type: none"> ■ IEEE 802.3 Compliant 10/100/1000 BaseT on Board <ul style="list-style-type: none"> ● Wake On LAN Supported
Integrated Wireless	<ul style="list-style-type: none"> ■ Mini-PCI WLAN 802.11 a/b/g Option <ul style="list-style-type: none"> ● Internal or External Antenna Placement
Display	<ul style="list-style-type: none"> ■ 15" TFT Active LCD >250 NIT Brightness <ul style="list-style-type: none"> ● 1024 x 768 XGA Resolution ● 16M Colors
Touchscreen	<ul style="list-style-type: none"> ■ 5-Wire Resistive <ul style="list-style-type: none"> ● Capacitive Touchscreen Option ● No Touchscreen Option
Power Supply	<ul style="list-style-type: none"> ■ Internal, Universal Input / Auto-Switching
Integrated Magnetic Stripe Reader	<ul style="list-style-type: none"> ■ 3 Track Serial TTL Interface <i>(internal)</i>
Audio	<ul style="list-style-type: none"> ■ Mic In, Line Out Ports ■ Integrated R/L Speakers Standard
Cash Drawer Ports	<ul style="list-style-type: none"> ■ 2 - MICROS 12/24 Volt Cash Drawer Ports
Serial Port	<ul style="list-style-type: none"> ■ 1 - 9 pin RS-232 Serial Port ■ 2 – RJ45 RS-232 Serial Port
IDN Port	<ul style="list-style-type: none"> ■ 1 – RJ45 RS422/RS485/RS232 Switchable Port – Labeled “Port A”
Customer Display Ports	<ul style="list-style-type: none"> ■ 1 – 4 Pin Mini-DIN Connector for MICROS Pole Display ■ 1 - 7 Pin Port Header for Integrated Customer Display Option ■ Optional Support for VGA 2nd Display <i>(WEPOS only)</i>
USB Ports	<ul style="list-style-type: none"> ■ 4 External USB V2.0
Mini-PCI Port	<ul style="list-style-type: none"> ■ Mini-PCI Port Provided to Support Integrated Wireless OR Second Graphics Card <i>(WEPOS only)</i>
Integrated Fingerprint Reader	<ul style="list-style-type: none"> ■ Optional – Optical USB
Dimensions	<ul style="list-style-type: none"> ■ 4.3" H x 15.40" W x 13.00" D
Weight	<ul style="list-style-type: none"> ■ 6.46kg/14.24lbs
Enclosure	<ul style="list-style-type: none"> ■ Rugged ABS Plastic Blend, Spill Resistant Enclosure. <i>(MICROSGrey)</i> Passive Cooling <i>(No fans)</i>
Operating Temp	<ul style="list-style-type: none"> ■ 0° C to 45° C
Certifications	<ul style="list-style-type: none"> ■ FCC Class A, UL, CE, CCC
Other	<ul style="list-style-type: none"> ■ RoHS Compliant Design

